D-ATIS
128.725
ARR NE 117.7
ARR SW 115.4
KENNEDY TOWER
RWYS 04R-22L and 13L-31R
119.1 281.55
RWYS 04L-22R and 13R-31L
123.9 281.55
GND CON
121.9 348.6
CLNC DEL
135.05 348.6
RAMP CON
125.05
CPDLC
PDC
D
AUX FIRE STATION
EMAS
ELEV 12
ELEV 13
22R
22L
223.6°
313.6°
8400 X 200
04L
04R
043.6°
CAT 2 HOLD
13L
31R
31L
7079 X 200
10000 X 200
133.6°
INTERNATIONAL ARRIVAL TERMINAL
U.S. CUSTOMS
TWR 338
197
FIRE STATION
GENERAL AVIATION TERMINAL
14511 X 200
13R
133.5°
73°49'W
73°48'W
73°47'W
73°46'W
73°45'W
40°39'N
40°38'N
FIELD ELEV 13
VAR 12.8° W
JANUARY 2020
ANNUAL RATE OF CHANGE
0.0° E
Runway Status Lights in Operation
ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces.
RWYS 04L-22R, 04R-22L
PCN 90 R/B/W/T
D-210, 2D-550, 2D/2D2-1100
RWY 13L-31R
PCN 148 R/A/W/T
D-210, 2D-550, 2D/2D2-1100
RWY 13R-31L
PCN 98 R/B/W/T
D-210, 2D-550, 2D/2D2-1100
CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.