

AIRPORT DIAGRAM

D-ATIS ARR 133.675

DEP 118.125

METRO TOWER

118.4 (RWY 03L-21R, 03R-21L, 27R)

128.75 (RWY 27L)

135.0 (RWY 04L-22R, 04R-22L)

317.725

CLNC DEL

120.65

CPDLC

PDC

D

RWY 03L-21R

PCN 86 R/B/W/T

S-120, D-250, 2D-550, 2D/2D2-1000

RWY 03R-21L

PCN 91 R/B/W/T

S-100, D-200, 2D-350, 2D/2D2-750

RWY 04L-22R

PCN 126 R/B/W/T

S-100, D-200, 2D-350, 2D/2D2-750

RWY 04R-22L

PCN 126 R/B/W/T

S-100, D-185, 2D-350

RWY 09L-27R

PCN 73 R/A/W/T

S-100, D-185, 2D-350

RWY 09R-27L

PCN 78 R/A/W/T

S-100, D-185, 2D-350

NORTHWEST
GND CON
121.8

U.S. CUSTOMS AND
GENERAL AVIATION

ILS HOLD

ELEV 636

CAT 2 HOLD

DE-ICE PAD

ELEV 631

NORTH
TERMINAL
D

ELEV 632

CAT 2 HOLD

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

ELEV 634

ELEV 632

JANUARY 2020
ANNUAL RATE OF CHANGE
0.0° W

Runway Status
Lights in operation.

10000 X 150

12003 X 200

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

10001 X 150

8500 X 150

SOUTHWEST
GND CON
132.725

ILS HOLD

ELEV 637

CAT 2 HOLD

DE-ICE PAD

SOUTH
TERMINAL
A

ELEV 636

CAT 2 HOLD

ELEV 633

CAT 2 HOLD

ELEV 633

SOUTHEAST
GND CON
119.25

FIELD
ELEV
645

ASDE-X in use. Operate transponders
with altitude reporting mode and ADSB
(if equipped) enabled on all airport surfaces.

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

EC-1, 18 APR 2024 to 16 MAY 2024

EC-1, 18 APR 2024 to 16 MAY 2024